

SKY CLIMBER of Hawaii

ELECTRICAL SPECIFICATIONS		
	Sgl Volt 1000 & 1250	Sgl Volt 1500
Power	1.3 HP / kW 0.95	1.5 HP / kW1.10
Line Current	9.0 Amps	9.00 Amps14/3
Power Cable	14/3	14/3
Voltage	208 Vac/80 Hz 1 PH	208 Vac/80 Hz 1 PH
Hoist Weight	100 lbs.	100 lbs.*
Sky Lock III	Included with hoist	Included with hoist
Wire Rope	5/16"	5/16"
Ascent Speed	32 fpm	32 fpm
Descent Speed	35 fpm	35 fpm
Pendent Ctrl	Hoist Mounted Ctrl w/Plug	Available
Part No.	KCE-1000-208	KCE-1500-208
Part No.	KCD-1250-208	*Weight includes Sky Lock

GENERATOR SELECTION GUIDE									RECOMMENDED			
									Generator KW		Generator KVA	
Qty	Hoist	Voltage	Run Amps	Run KVA	Run KW	Start Amps	Start KVA	Start KW	20% added	KW	20% added	KVA
1	Compact 1000	208	9.0	1.82	3.2400	21	4.37	7.57	3.89	4	2.184	3
2	Compact 1000	208	18.0	3.74	6.4800	42	8.74	15.13	7.78	8	4.488	5
1	Compact 1250	208	9.0	1.82	3.2400	21	4.37	7.57	3.89	4	2.184	3
2	Compact 1250	208	18.0	3.74	6.2400	42	8.74	15.13	7.78	8	4.488	5
1	Compact 1500	230	7.5	1.73	2.9877	21	4.83	8.37	3.59	4	2.070	3
2	Compact 1500	230	15.0	3.45	5.9754	42	9.66	16.73	7.17	8	4.140	5

Sky Climber of Hawaii, LLC
Honolulu, Hi 96819
Ph: 808-845-1777
sch@skyclimberhawaii.com

SKY CLIMBER
of Hawaii